

L11 ANSWER 20 OF 41 CA COPYRIGHT 2008 ACS on STN

AN 122:272330 CA

OREF 122:49545a,49548a

ED Entered STN: 27 May 1995

TI High-flowability cement compositions

IN Hayakawa, Kazuhisa; Kobayashi, Kazuto

PA Shinetsu Chemical Industry Co., Ltd., Japan

SO Jpn. Kokai Tokkyo Koho, 8 pp.

CODEN: JKXXAF

DT Patent

LA Japanese

IC ICM C04B028-02

ICS C04B024-04; C04B024-22; C04B024-32; C04B024-38

ICI C04B028-02, C04B014-06, C04B016-02, C04B016-06, C04B024-38, C04B024-22, C04B024-32; C04B103-40

CC 58-1 (Cement, Concrete, and Related Building Materials)

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 07033502	A	19950203	JP 1993-224922	19930726
	JP 3101788	B2	20001023		
PRAI	JP 1993-224922		19930726		

CLASS

PATENT NO.	CLASS	PATENT FAMILY CLASSIFICATION CODES
JP 07033502	ICM	C04B028-02
	ICS	C04B024-04; C04B024-22; C04B024-32; C04B024-38
	ICI	C04B028-02, C04B014-06, C04B016-02, C04B016-06, C04B024-38, C04B024-22, C04B024-32; C04B103-40
	IPCI	C04B0028-02 [ICM,6]; C04B0024-04 [ICS,6]; C04B0024-22 [ICS,6]; C04B0024-32 [ICS,6]; C04B0024-38 [ICS,6]; C04B0028-02 [ICI,6]; C04B0028-00 [ICI,6,C*]; C04B0014-06 [ICI,6]; C04B0014-02 [ICI,6,C*]; C04B0016-02 [ICI,6]; C04B0016-06 [ICI,6]; C04B0016-00 [ICI,6,C*]; C04B0024-38 [ICI,6]; C04B0024-22 [ICI,6]; C04B0024-32 [ICI,6]; C04B0024-00 [ICI,6,C*]; C04B0103-40 [ICI,6]
	IPCR	C04B0024-04 [I,A]; B28B0003-20 [I,C*]; B28B0003-20 [I,A]; C04B0024-00 [I,C*]; C04B0024-08 [I,A]; C04B0024-22 [I,A]; C04B0024-32 [I,A]; C04B0024-38 [I,A]; C04B0028-00 [I,C*]; C04B0028-02 [I,A]; C04B0103-40 [N,A]
	BCLA	C04B028/02

AB Into cement-based compns. containing a dispersant comprising aryl sulfonate (with or without alkyl substitution)-H<sub>2</sub>CO condensate, cellulose-based binder and water, a nonionic surfactant derived from higher fatty acids is added. Thus, a composition comprising cement 70, silica powder 30, pulp 4.5, polypropylene fiber 0.5, hydroxypropylmethylcellulose 1.0,  $\beta$ -naphthalenesulfonic acid-formalin condensate 0.3, polyoxyethylene monooleate 0.02, and water 22 parts was extruded and autoclaved at 170° for 8 h to give a concrete having bending strength 310 kg/cm<sup>2</sup>.

ST nonionic surfactant fatty acid cement